









PRODUCT CODE

Downlight Only

Uplight Only

Length (565mm)

Length (845mm)

Length (1125mm)

Standard Driver

Dali Driver

Wireless Dim

Touch Dimming Driver 2000 Lumens (565mm)

3000 Lumens (845mm)

4000 Lumens (1125mm)

2000 Lumens (565mm)

3000 Lumens (845mm)

4000 Lumens (1124mm)

3000 Lumens (565mm)

5000 Lumens (845mm)

7000 Lumens (1125mm)

3000 Kelvin

4000 Kelvin No Sensor

PIR Sensor No Emergency

Opal

White

Black

Silver

Gold

Microprism

Other/Specified

3 Hour Emergency

Lithium Emergency

Self-Test 3 Hour Emergency

3 Hour Emergency DALI EM Pro

1-10V Driver

Uplight / Downlight

Tower Uplight / Downlight

WLM Meridian Wall

D

U

Χ

06

80

11

S

D

W

Α

03

04

02

03

04

03

05

07

3

4

 ${\sf PR}$

EL

ST

ED

IM

OP

MP

W

В

S

G

0

Product

Distribution

Body Size

Driver

Output (downlight only)

Output

(uplight only)

Output (up/downlight)

Colour Temperature

Emergency*

Diffuser

Body Colour

Sensor

MERIDIAN WL Wall Mounted Linear System

MANUFACTURING IN THE UNITED KINGDOM

- Extruded aluminium housing
- Double height (Tower) version available
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Multiple coloured diffuser inserts available
- Comes complete with mounting brackets
- Downlight only or up/downlight

- High colour consistency 3 step
- High colour rendering CRI>80
- Various powder coated finishes
- Bespoke sizes/outputs made to order
- Wireless option available
- Emergency options available

•	Stand alone or continuous run
	liahtina system

- MacAdam

- IP20 rated
- 5 year warranty on LED system

79mm	-	——565mm to 1125mm	94mm 1
79mm	215mm 285mm to 1125mm	Tower dimensions only	

*Not available in all body sizes

Ambient operating temperature 25°C







