





## LANDO SPORT

### Wire Guarded High/Low Bay

MANUFACTURING IN THE  
UNITED KINGDOM 

- Built to withstand the rigours of sports hall activities
- Body constructed from powder coated steel with a protective wire ball guard
- High transmission opal diffuser
- Tridonic or Philips LED modules and drivers
- Comes complete with GST panel mounted plug
- Efficacies of over 130 luminaire lumens per watt
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- Various additional mounting brackets available
- IP20 rated
- Wireless option available
- Dual circuit option available
- LiFePO4 Lithium Battery for extended emergency life
- 5 year warranty on LED system



Ambient operating temperature 25°C

| PRODUCT CODE              |     |                              |
|---------------------------|-----|------------------------------|
| Product                   | LSP | Lando Sport                  |
| Body Size                 | 4   | 435mm (12-24)                |
|                           | 6   | 540mm (28-36)                |
|                           | 8   | 640mm (38-48)                |
| Driver                    | S   | Standard Driver              |
|                           | D   | Dali Driver                  |
|                           | W   | Wireless Dim                 |
|                           | A   | 1-10V Driver                 |
|                           | T   | Touch Dimming Driver         |
| Output                    | 12  | 12500 Lumens                 |
|                           | 14  | 13900 Lumens                 |
|                           | 16  | 16300 Lumens                 |
|                           | 18  | 18700 Lumens                 |
|                           | 21  | 21000 Lumens                 |
|                           | 24  | 24400 Lumens                 |
|                           | 28  | 28100 Lumens                 |
|                           | 30  | 29800 Lumens                 |
|                           | 33  | 33200 Lumens                 |
|                           | 36  | 36600 Lumens                 |
|                           | 38  | 37500 Lumens                 |
|                           | 40  | 39700 Lumens                 |
|                           | 42  | 42000 Lumens                 |
|                           | 47  | 46500 Lumens                 |
|                           | 49  | 48800 Lumens                 |
| Colour Temperature        | 3   | 3000 Kelvin                  |
|                           | 4   | 4000 Kelvin                  |
|                           | 5   | 5000 Kelvin                  |
| Sensor                    | -   | No Sensor                    |
|                           | PL  | PIR Low (up to 3.5m)         |
|                           | PM  | PIR Mid (up to 12m)          |
|                           | PH  | PIR High (up to 16m)         |
| Emergency Lithium LiFePO4 | -   | No Emergency                 |
|                           | EL  | 3 Hour Emergency             |
|                           | EX  | High Output 3 Hour Emergency |
|                           | ST  | Self-Test 3 Hour Emergency   |
|                           | ED  | DALI EM Pro 3 Hour Emergency |
| Diffuser                  | OP  | Opal                         |
|                           | MP  | Microprism                   |
| Body Colour               | W   | White                        |
|                           | B   | Black                        |