





MERIDIAN RC Recessed Linear System

MANUFACTURING IN THE
UNITED KINGDOM 

- Extruded aluminium housing
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Stand alone or continuous run lighting system
- Lit corner and T section available
- Infill sections and blanking panels available
- Multiple coloured diffuser inserts available
- Bespoke sizes, shapes and outputs made to order
- Various powder coated finishes
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- IP20 rated
- Wireless option available
- LiFePO4 Lithium Battery for extended emergency life
- 5 year warranty on LED system



Ambient operating temperature 25°C

**Emergency option not available

PRODUCT CODE		
Product	MRC	Meridian Recessed
Body Size*	06	Length (565mm)**
	08	Length (845mm)
	11	Length (1125mm)
	14	Length (1405mm)
	17	Length (1685mm)
	20	Length (1965mm)
	23	Length (2250mm)
	28	Length (2810mm)
Configuration	SA	Stand Alone
	CC	Continuous Centre
	CS	Continuous Start
	CE	Continuous End
Driver	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
	T	Touch Dimming Driver
Output	02	2100 Lumens (565mm)**
	03	3100 Lumens (845mm)
	04	4200 Lumens (1125mm)
	05	5200 Lumens (1405mm)
	06	6300 Lumens (1685mm)
	07	7400 Lumens (1965mm)
	08	8400 Lumens (2250mm)
Colour Temperature	3	3000 Kelvin
	4	4000 Kelvin
Sensor	-	No Sensor
	PR	PIR Sensor
Emergency Lithium LiFePO4	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
	ED	DALI EM Pro 3 Hour Emergency
Diffuser	OP	Opal
	MP	Microprism
Body Colour	W	White
	B	Black
	S	Silver
	O	Other/Specified

*Measurements do not include trim - Add 30mm to the overall length of fitting (standalone and continuous run)

