




MERIDIAN WL

Wall Mounted Linear System


MANUFACTURING IN THE
UNITED KINGDOM 

- Extruded aluminium housing
- Double height (Tower) version available
- Vertical mounting version available
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Downlight, up/downlight & uplight only options
- Multiple coloured diffuser inserts available
- Bespoke sizes, and outputs made to order
- Various powder coated finishes
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- IP20 rated
- Wireless option available
- LiFePO4 Lithium Battery for extended emergency life
- 5 year warranty on LED system

- Wall



- Tower Wall



Ambient operating temperature 25°C

PRODUCT CODE		
Product	WLM	Meridian Wall
Distribution	D	Downlight Only
	U	Uplight / Downlight
	X	Uplight Only
	T	Tower Uplight / Downlight
Body Size	06	Length (565mm)**
	08	Length (845mm)
	11	Length (1125mm)
Driver	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
	T	Touch Dimming Driver
Output (downlight only)	02	2100 Lumens (565mm)**
	03	3100 Lumens (845mm)
	04	4200 Lumens (1125mm)
Output (uplight only)	02	2100 Lumens (565mm)**
	03	3100 Lumens (845mm)
	04	4200 Lumens (1125mm)
Output (up/downlight)	04	4200 Lumens (565mm)**
	06	6200 Lumens (845mm)
	08	8400 Lumens (1125mm)
Colour Temperature	3	3000 Kelvin
	4	4000 Kelvin
Sensor	-	No Sensor
	PR	PIR Sensor
Emergency Lithium LiFePO4	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
	ED	DALI EM Pro 3 Hour Emergency
Diffuser	OP	Opal
	MP	Microprism
Body Colour	W	White
	B	Black
	S	Silver
	G	Gold
	O	Other/Specified

**Emergency option not available unless Tower option (T) selected