




UNIVERSAL IP Moisture Resistant Recessed

MANUFACTURING IN THE
UNITED KINGDOM 

- Body constructed from powder coated steel
- High transmission opal diffuser
- Microprism diffuser available to aid in achieving UGR<19
- Diffuser retained with screws
- Tridonic or Philips LED modules and drivers
- Suitable for 15mm/25mm T & plasterboard ceiling types as standard
- Concealed T ceiling option available
- Clean room option available
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- Bespoke sizes and outputs made to order
- Available with tamper proof screws
- Various powder coated finishes
- Wireless option available
- LiFePO4 Lithium Battery for extended emergency life
- IP65 from below the ceiling
- 5 year warranty on LED system



PRODUCT CODE		
Product	UMIP	Universal IP65
Body Size	66	595mm X 595mm
	123	1195mm X 295mm
	126	1195mm X 595mm
Driver	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
	T	Touch Dimming Driver
Output (66) Output (123)	03	3300 Lumens
	04	3800 Lumens
	05	5000 Lumens
	06	6100 Lumens
	07	6600 Lumens
	08	7700 Lumens
Output (126)	10	10000 Lumens
	12	12200 Lumens
Colour Temperature	3	3000 Kelvin
	4	4000 Kelvin
	5	5000 Kelvin
Sensor	-	No Sensor
	PR	Pir Sensor
	MW	Microwave Sensor
Emergency Lithium LiFePO4	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
	ED	DALI EM Pro 3 Hour Emergency
Diffuser	OP	Opal
	MP	Microprism
Body Colour	W	White
	B	Black
	S	Silver
	O	Other/Specified

Ambient operating temperature 25°C

