









ACADEMY Surface Linear

- Designed specifically for schools, hospitals and similar environments
- Body constructed from powder coated steel
- Opal polycarbonate TPA rated diffuser for general illumination

- MANUFACTURING IN THE UNITED KINGDOM
- Various powder coated finishes
- Wireless option available
- Optional LiFePO4 Lithium Battery for extended life
- Tridonic or Philips LED modules and drivers
- IP20 rated
- 5 year warranty on LED system

PRODUCT CODE		
Product	ACA	Academy Linear LED
Body Size	11	1170mm Length
	14	1450mm Length
Drivers	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	Α	1-10V Driver
	Т	Touch Dimming Driver
	04	4200 Lumens
Output (11)	05	4900 Lumens
	06	6100 Lumens
Output (14)	06	6100 Lumens
	07	7100 Lumens
	80	8200 Lumens
Colour	3	3000 Kelvin
Temperature	4	4000 Kelvin
Sensor	-	No Sensor
	PR	PIR Sensor
	TS	Thumb Sensor
	MW	Microwave Sensor
Emergency	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
	ED	3 Hour Emergency Dali EM Pro
	LM	Lithium Emergency
	W	White
Body Colour	В	Black

Other/Specified

	105mm	
E C C C C C C C C C C C C C C C C C C C		187
-	1170mm — 1450mm	-

Ambient operating temperature 25°C





