contrac L i g h t i n g





SOFTLUX 8 Direct/Indirect Recessed

- Body constructed from powder coated steel
- High transmission opal diffuser
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Suitable for 15mm/25mm T ceiling types as standard
- Pull-up and Concealed T ceiling versions available


MANUFACTURING IN THE UNITED KINGDOM

- Bespoke/project specific sizes, and outputs made to order
- Various powder coated finishes
- Wireless option available
- Optional LiFePO4 Lithium Battery for extended life
- IP20 rated
- 5 year warranty on LED system





PRODUCT CODE		
Product	S8I	Softlux 8
Mounting	RC	Recessed Lift & Tilt
	UM	Recessed Pull Up
Body Size	66	595mm X 595mm
Driver	S	Standard Driver
	D	Dali Driver
	W	Wireless
	А	1-10V Driver
	Т	Touch Dimming Driver
Output	04	4200 Lumens
	05	4900 Lumens
	06	6100 Lumens
	07	6800 Lumens
	08	7900 Lumens
Colour Temperature	30	3000 Kelvin
	40	4000 Kelvin
Sensor	-	No Sensor
	MS	Mini Sensor
Emergency	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
	ED	3 Hour Emergency DALI EM Pro
	LM	Lithium Emergency
Diffuser	OP	Opal
	MP	Microprism
Body Colour	W	White
	В	Black
	S	Silver
	С	Custom



Ambient operating temperature 25°C - Do not cover back of fitting

