




MERIDIAN SF

Surface Mounted Linear System

MANUFACTURING IN THE
UNITED KINGDOM

- Extruded aluminium housing
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Multiple coloured diffuser inserts available
- Infill blanking panels optional
- Stand alone or continuous run lighting system
- Lit corner section made to order
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- Bespoke/project specific sizes, shapes and outputs made to order
- Various powder coated finishes
- IP20 rated
- Wireless option available
- Optional LiFePO4 Lithium Battery for extended life
- 5 year warranty on LED system



Ambient operating temperature 25°C

PRODUCT CODE		
Product	MSF	Meridian Surface
Body Size	06	Length (565mm)
	08	Length (845mm)
	11	Length (1125mm)
	14	Length (1405mm)
	17	Length (1685mm)
	23	Length (2250mm)
Configuration	28	Length (2810mm)
	SA	Stand Alone
	CC	Continuous Centre
	CS	Continuous Start
Driver	CE	Continuous End
	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
Output	T	Touch Dimming Driver
	02	2000 Lumens (565mm)
	03	3000 Lumens (845mm)
	04	4000 Lumens (1125mm)
	05	5000 Lumens (1405mm)
	06	6000 Lumens (1685mm)
Colour Temperature	08	8000 Lumens (2250mm)
	10	10000 Lumens (2810mm)
Sensor	3	3000 Kelvin
	4	4000 Kelvin
Emergency	-	No Sensor
	PR	PIR Sensor
	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
Diffuser	ED	3 Hour Emergency DALI EM Pro
	LM	Lithium Emergency
	OP	Opal
Body Colour	MP	Microprism
	W	White
	B	Black
	S	Silver
	G	Gold
	O	Other/Specified






MERIDIAN SF HO

Surface Mounted Linear System

MANUFACTURING IN THE
UNITED KINGDOM

- Extruded aluminium housing
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Multiple coloured diffuser inserts available
- Infill blanking panels optional
- Stand alone or continuous run lighting system
- Lit corner section made to order
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- Bespoke/project specific sizes, shapes and outputs made to order
- Various powder coated finishes
- IP20 rated
- Wireless option available
- Optional LiFePO4 Lithium Battery for extended life
- 5 year warranty on LED system



Ambient operating temperature 25°C

PRODUCT CODE		
Product	MSF	Meridian Surface Ho
Body Size	06	Length (565mm)
	08	Length (845mm)
	11	Length (1125mm)
	14	Length (1405mm)
	17	Length (1685mm)
	23	Length (2250mm)
Configuration	28	Length (2810mm)
	SA	Stand Alone
	CC	Continuous Centre
	CS	Continuous Start
Driver	CE	Continuous End
	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
Output	T	Touch Dimming Driver
	03	3000 Lumens (565mm)
	04	4500 Lumens (845mm)
	06	6100 Lumens (1125mm)
	07	7600 Lumens (1405mm)
Colour Temperature	09	9100 Lumens (1685mm)
	12	12200 Lumens (2250mm)
	15	15200 Lumens (2810mm)
Sensor	3	3000 Kelvin
	4	4000 Kelvin
Emergency	-	No Sensor
	PR	PIR Sensor
	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
Diffuser	ED	3 Hour Emergency DALI EM Pro
	LM	Lithium Emergency
	OP	Opal
Body Colour	MP	Microprism
	W	White
	B	Black
	S	Silver
	G	Gold
	O	Other/Specified




MERIDIAN SF LO

Surface Mounted Linear System

MANUFACTURING IN THE
UNITED KINGDOM

- Extruded aluminium housing
- Snap in/out opal diffuser for general illumination
- Microprism diffuser available to aid in achieving UGR<19
- Tridonic or Philips LED modules and drivers
- Multiple coloured diffuser inserts available
- Infill blanking panels optional
- Stand alone or continuous run lighting system
- Lit corner section made to order
- High colour consistency 3 step MacAdam
- High colour rendering CRI>80
- Bespoke/project specific sizes, shapes and outputs made to order
- Various powder coated finishes
- IP20 rated
- Wireless option available
- Optional LiFePO4 Lithium Battery for extended life
- 5 year warranty on LED system



Ambient operating temperature 25°C

PRODUCT CODE		
Product	MSF	Meridian Surface Lo
Body Size	06	Length (565mm)
	08	Length (845mm)
	11	Length (1125mm)
	14	Length (1405mm)
	17	Length (1685mm)
	23	Length (2250mm)
Configuration	28	Length (2810mm)
	SA	Stand Alone
	CC	Continuous Centre
	CS	Continuous Start
Driver	CE	Continuous End
	S	Standard Driver
	D	Dali Driver
	W	Wireless Dim
	A	1-10V Driver
Output	T	Touch Dimming Driver
	01	1000 Lumens (565mm)
	015	1600 Lumens (845mm)
	02	2100 Lumens (1125mm)
	025	2700 Lumens (1405mm)
	03	3200 Lumens (1685mm)
Colour Temperature	04	4200 Lumens (2250mm)
	05	5400 Lumens (2810mm)
Sensor	3	3000 Kelvin
	4	4000 Kelvin
Emergency	-	No Sensor
	PR	PIR Sensor
	-	No Emergency
	EL	3 Hour Emergency
	ST	Self-Test 3 Hour Emergency
Diffuser	ED	3 Hour Emergency DALI EM Pro
	LM	Lithium Emergency
	OP	Opal
Body Colour	MP	Microprism
	W	White
	B	Black
	S	Silver
	G	Gold
	O	Other/Specified